

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A guiding device which guides a user, said guiding device comprising:

an acquisition unit operable to acquire a guiding route for the user;

a recognition unit operable to recognize an object which exists in the vicinity of the user;

a management unit operable to manage an object and an adjustment method for adjusting an influence that the object has on an action of the user, by associating the object and the adjustment method in advance;

a judgment unit operable to judge whether or not the object recognized by said recognition unit exists within the guiding route acquired by said acquisition unit; and

an adjustment unit operable to adjust an extent to which the user shows resistance to the object ~~execute a specified adjustment process~~ based on a result obtained by said judgment unit, and on the adjustment method managed in association with the object recognized by said recognition unit.

2. (Original) The guiding device according to Claim 1,

wherein said adjustment unit is operable to augment an extent to which the object attracts the user, in the case where the object is judged to exist within the guiding route.

3. (Original) The guiding device according to Claim 1,

wherein said adjustment unit is operable to reduce an extent to which the user shows

resistance to the object, in the case where the object is judged to exist within the guiding route.

4. (Original) The guiding device according to Claim 1,
wherein said adjustment unit is operable to reduce an extent to which the object attracts the user, in the case where the object is judged not to exist within the guiding route.

5. (Original) The guiding device according to Claim 1,
wherein said adjustment unit is operable to augment an extent to which the user shows resistance to the object, in the case where the object is judged to not exist within the guiding route.

6. (Original) The guiding device according to Claim 1,
wherein said adjustment unit is a head mounted display which is operable to present a specified image to the user by making the specified image overlap the object, or outlining an area around the object.

7. (Original) The guiding device according to Claim 1,
wherein said adjustment unit is a head mounted display operable to present a specified audio to the user so that the specified audio is audible from the direction of the object, or to prevent the specified audio from being audible from the direction of the object.

8. (Original) The guiding device according to Claim 1,
wherein said adjustment unit is a projector which is operable to project an image onto the
object.

9. (Original) The guiding device according to Claim 1,
wherein said adjustment unit is an air-conditioning device operable to make the object
conduct an air flow.

10. (Original) The guiding device according to Claim 1,
wherein said management unit is operable to manage one of an attraction list which is a
collection of phenomena that influence an extent to which the user is attracted, and a resistance
list which is a collection of phenomena which influence an extent to which the user shows
resistance; and
said adjustment unit is operable to cause a phenomenon included in one of the attraction
list and the resistance list to occur.

11. (Original) The guiding device according to Claim 10, further comprising
a history accumulation unit operable to accumulate an action history of the user,
wherein said management unit is operable to update contents of one of the attraction list
and the resistance list to contents reflecting a preference of the user, based on the action history
of the user accumulated in said history accumulation unit.

12. (Currently Amended) A guiding method of guiding a user, said guiding method comprising:

- an acquisition step of acquiring a guiding route for the user;
- a recognition step of recognizing an object which exists in the vicinity of the user;
- an association step of associating in advance an object and an adjustment method for adjusting an influence that the object has on an action of the user;
- a judgment step of judging whether or not the object recognized in said recognition step exists within the guiding route acquired in said acquisition step; and
- an adjustment step of adjusting an extent to which the user shows resistance to the object ~~executing a specified adjustment process~~ based on a result obtained in said judgment step, and on the adjustment method managed in association with the object recognized in said recognition step.

13. (Canceled)

14. (Currently Amended) A computer-readable storage medium in which a program for guiding a user is stored,

wherein the program causes a computer to execute a method comprising:

- an acquisition step of acquiring a guiding route for the user;
- a recognition step of recognizing an object which exists in the vicinity of the user;
- an association step of associating in advance an object and an adjustment method for

adjusting an influence that the object has on an action of the user;

a judgment step of judging whether or not the object recognized in said recognition step exists within the guiding route acquired in said acquisition step; and

an adjustment step of adjusting an extent to which the user shows resistance to the object
~~executing a specified adjustment process~~ based on a result obtained in said judgment step, and on the adjustment method managed in association with the object recognized in said recognition step.

15. (Currently Amended) An integrated circuit which guides a user, said integrated circuit comprising:

an acquisition unit operable to acquire a guiding route for the user;

a recognition unit operable to recognize an object which exists in the vicinity of the user;

a management unit operable to manage an object and an adjustment method for adjusting an influence that the object has on an action of the user, by associating the object and the adjustment method in advance;

a judgment unit operable to judge whether or not the object recognized by said recognition unit exists within the guiding route acquired by said acquisition unit; and

an adjustment unit operable to adjust an extent to which the user shows resistance to the object
~~execute a specified adjustment process~~ based on a result obtained by said judgment unit, and on the adjustment method managed in association with the object recognized by said recognition ~~step~~ unit.